



**NOTES:**

1. -ALL SIZES & DIMENSIONS ARE NOMINAL
2. - MIN 1/4" JOINTS FOR DRY-LAY. WET-LAY USE MIN 1/2" JOINTS
3. -REFER TO INSTALLATION INSTRUCTIONS FOR DETAILS ON WET-LAY & DRY-LAY APPLICATIONS
4. - ANNUAL APPLICATION OF SEALER IS REQUIRED AFTER PRODUCT IS INSTALLED TO PROTECT COLOUR
5. - DO NOT USE PLATE TAMPER ON STONE
6. - DO NOT USE RUBBER Mallet TO LEVEL STONES

**CREDIT VALLEY- SANDSTONE®**

2 SIZE PATTERN

SCALE: NTS

**CV-7.5**



137 VINYL COURT, WOODBRIDGE, ONTARIO, L4L 4A3  
 T. 905.850.8430 F. 905.850.2302  
 TF. 1.800.854.0072  
 WWW.STONE-LINK.COM

NOTES:  
 ALL SIZES & DIMENSIONS ARE APPROXIMATE  
 DIMENSIONS INDICATED ARE NOMINAL  
 REFER TO CATALOGUE PRODUCT SPECIFICATIONS FOR ACTUAL  
 DIMENSIONS.  
 APPROXIMATE SQ FT IS BASED ON NOMINAL DIMENSIONS