



NOTES:

1. -ALL SIZES & DIMENSIONS ARE NOMINAL
2. - MIN 1/4" JOINTS FOR DRY-LAY. WET-LAY USE MIN 1/2" JOINTS
3. -REFER TO INSTALLATION INSTRUCTIONS FOR DETAILS ON WET-LAY & DRY-LAY APPLICATIONS
4. - ANNUAL APPLICATION OF SEALER IS REQUIRED AFTER PRODUCT IS INSTALLED TO PROTECT COLOUR
5. - DO NOT USE PLATE TAMPER ON STONE
6. - DO NOT USE RUBBER Mallet TO LEVEL STONES

GEORGIAN BAY FLAGSTONE®-CORNER KIT
3 SIZE EXPANDABLE PAVING SYSTEM

SCALE: NTS

GBC-2.3



137 VINYL COURT. WOODBRIDGE, ONTARIO, L4L 4A3
T. 905.850.8430 F. 905.850.2302
TF. 1.800.854.0072
WWW.STONE-LINK.COM

NOTES:
ALL SIZES & DIMENSIONS ARE APPROXIMATE
DIMENSIONS INDICATED ARE NOMINAL
REFER TO CATALOGUE PRODUCT SPECIFICATIONS FOR ACTUAL
DIMENSIONS.
APPROXIMATE SQ FT IS BASED ON NOMINAL DIMENSIONS